TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

ı

Ī

١

1

ı

Ī

Т

IMPORTANT:
THIS DRAWING SHALL BE USED IN
COMBINATION WITH THE GENERAL
NOTES MD 104.00-01 - MD 104.00-18 AND
STANDARD DETAILS MD 104.01-01 MD 104.01-62

NOTES:

MOWING OPERATIONS

MOWERS SHALL HAVE FLASHING WARNING LIGHTS MOUNTED ON THEM.

THE MOWERS AHEAD SIGN SHOULD BE USED TO WARN OF MOWING CREWS UNLESS MOWER(S) ARE EQUIPPED WITH TWO 360° FLASHING/ROTATING AMBER LIGHTS OR TWO 360° FLASHING DOME LIGHTS, THE DECISION SIGHT DISTANCE IS MET FOR THE RATES OF SPEED SHOWN ON STANDARD NO. MD 104,00-03, AND MOWER(S) WILL NOT BE TRAVELLING IN ANY OF THE FOLLOWING THREE CONDITIONS:

- WITHIN 15 FT. OF THE EDGE LINE OF THE ROADWAY OR ON THE SHOULDER
- IN THE ROADWAY ON A NARROW STRETCH OF ROADWAY OR TO GET AROUND A HIGHWAY STRUCTURE OR APPURTENANCE OR OTHER SUCH STRUCTURE
- _ ACROSS THE ROADWAY

MOWERS MAY NOT PROCEED MORE THAN 2 MILES AWAY FROM ADVANCE WARNING SIGN(S).

MOWERS WITHIN 15 FT. OF THE EDGE LINE SHALL TRAVEL IN THE SAME DIRECTION AS ADJACENT

OTHER OPERATIONS

THE SURVEY CREW SIGN SHOULD BE USED TO WARN OF SURVEYING CREWS WORKING IN OR ADJACENT TO THE ROADWAY.

THE WORKERS SYMBOL SIGN SHOULD BE USED TO WARN OF OTHER MOBILE OPERATIONS NOT RELATED TO MOWING OR SURVEYING ACTIVITIES. AND FOR WHICH NO MOBILE TYPICAL APPLICATION CURRENTLY EXISTS.

KEY:





DIRECTION OF TRAFFIC



WORK SITE

CATEGORY CODE ITEMS
M

SKA StateHighway

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY			
APPROVAL •	SHA	APPROVAL	• FEDERAL
REVISIONS		HIGHWAY AD	MINISTRATION
APPROVAL	8-20-03	APPROVAL	9-23-03
REVISED		REVISED	
REVISED		REVISED	
BE/ISED		DEMOED	

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

OR

SURVEY

MOWERS

AHEAD

NEXT 2 MILES 0R

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

MOBILE WORK OPERATION /MULTILANE UNDIV.
ALL SPEEDS

STANDARD NO.

MD 104.03-17